




# ACCURI PRO™



COLOR REFRACTIVE INDEX (Optional)  
80 / 90 / 95  
REFLECTOR BEAM  
15° / 24° / 40° / 60°



ACCURI PRO WHITE

COB [F] 10W  
3000K - 910lm / 5700K-960  
95mm  
D108 x H106mm

5501 60 2001 10

COB [F] 14W  
3000K - 1260lm / 5700K-1325  
95mm  
D108 x H106 mm

5501 60 2001 14



ACCURI PRO GOLD

COB [F] 10W  
3000K - 915lm / 5700K-960  
95mm  
D108x H106 mm

5501 60 2002 10

COB [F] 14W  
3000K - 1220lm / 5700K-1281  
95mm  
D108 x H106 mm

5501 60 2002 14



ACCURI PRO BLACK

COB [F] 10W  
3000K - 890lm / 5700K-935  
95mm  
D108 x H106 mm

5501 60 2003 10

COB [F] 14W  
3000K - 1190lm / 5700K-1210  
95mm  
D108 x H106 mm

5501 78 2003 14



REQUIREMENTS  
PSU EXT.  
CONNECTED POWER SUPPLY  
180 ~ 230 VAC



REQUIREMENTS  
PSU EXT.  
CONNECTED POWER SUPPLY  
180 ~ 230 VAC



REQUIREMENTS  
PSU EXT.  
CONNECTED POWER SUPPLY  
180 ~ 230 VAC

