




## PIEDRA SURFACE™



COLOR REFRACTIVE INDEX (Optional)  
80  
REFLECTOR BEAM  
90°



PIEDRA SURFACE BLACK

LED [CR] 12W  
3000K - 1080lm / 5700K-1170 S D130 x H100 mm

5501 90 2001 12

LED [F] 20W  
3000K - 1800lm / 5700K-1890 S D165 x H115 mm

5501 90 2001 20

LED [F] 30W / CRI 80  
3000K - 2650lm / 5700K-2782 S D200 x H130mm

5501 90 2001 30



PIEDRA SURFACE WHITE

LED [CR] 12W  
3000K - 1080lm / 5700K-1170 S D130 x H100 mm

5501 90 2002 12

LED [F] 20W  
3000K - 1800lm / 5700K-1890 S D165 x H115 mm

5501 90 2002 20

LED [F] 30W / CRI 80  
3000K - 2650lm / 5700K-2782 S D200 x H130 mm

5501 90 2002 30



III  $\frac{0.3}{\square}$  CE

REQUIREMENTS  
PSU LFLU-XX  
CONNECTED POWER SUPPLY  
110 ~ 230 VAC

III  $\frac{0.3}{\square}$  CE

REQUIREMENTS  
PSU LFLU-XX  
CONNECTED POWER SUPPLY  
110 ~ 230 VAC